



Rahman Industries Ltd.

EVO PRO



www.safetix.co.in



Upper	Buff CG Breathable Leather
Toe Cap	Imported Steel Toe Cap
Lining	Highly Breathable Micro-Porous Mesh
Sole	PU Single Density B52 (Black)
Size	39-50

### Industries Served

Automobile, Cement, Engineering, Airport Security, Oil & Gas, Process & Chemicals, Pharmaceuticals and Bio Technology



## PROTECTIVE FEATURES



### 100% Real Buffalo Leather

Genuine MHC CG Breathable Leather



### Steel Toe Cap

Protection to the foot against the falling objects with ability to withstand impact of 200J & 15 KN Compression in accordance with IS 15298 & EN 20345



### Oil & Chemical Resistant Sole

Single Density PU Sole offers protection in work surfaces having Oil & Mild Chemical Spills.



### Slip Resistant Sole

Excellent Sole design with unique open cleats offers protection against any slip hazard on wet & slippery work surfaces

## Key Features



High Strength, Abrasion Resistant & Breathable Leather upper and lining offers aesthetic look, moisture absorption capability and longer life.



Extra Wide Steel Toe Cap offers comfort by no crowding of toes.



Light Weight Shoe provides optimum safety and comfort for fatigue free working.



Thermo-Plastic Moulded Counter Stiffener offers excellent shape retaining which in turn provides more comfort.



4 Eyelets for excellent strength.



20 J Shock Absorption, heel spreads the pressure over a larger surface area which protects the joints & prevent during long hour of standing.



[www.safetix.co.in](http://www.safetix.co.in)

## EVO PRO

Component	Specification	Advantage
Upper	Buff CG Breathable Leather	Aesthetic look, Comfortable, Easy Air Exchange
	Thickness 1.8 - 2.0 mm	High Tensile Strength, Durable & longer life
Lining	Micro-Porous Mesh	Highly Breathable, High perspiration absorption, Quick Drying & Comfortable
Sock	Cambrell laminated with Moulded EVA	Full length extra comfort & cushioning,
Insole	Non-Woven	Flexible and better quality of water absorption and desorption, Antistatic.
Sole	Single Density PU with open cleated design & 20J shock absorption heel	Light weight & SRC Slip Resistant. Abrasion & Flex Resistant. Resistant to Fuel Oil. Can withstand high temperature upto 120°C for 1 minute. 20J Shock absorption heel prevents injuries to joints by spreading the load.
Toe Cap	200J Steel Toe Cap Imported Meeting EN 12568	Withstand 15 KN Compression & 200J Impact as per IS 15298 & EN 20345 standards.
Counter/Stiffener	Heat Activated Moulded Thermo-plastic	Excellent Shape retention for extra comfort.
Thread	Nylon	Chemical Resistant & Rot Free for better breaking strength.
Eyelets/D-Rings/Hooks/Loops	4 Eyelets	For Excellent Strengthening.
Laces	Nylon Cotton Round Laces	High Breaking Strength.

Membre du



E : [info@safetix.co.in](mailto:info@safetix.co.in)

